

RM Series Oil-Flooded Rotary Screw Compressors

30-75 kW



Reliability · Efficiency · Energy-saving

The Intelligence You Need To Move Your Business Forward

Ingersoll Rand works to keep you ahead of your competition with advanced compressed air systems that boost productivity, lower operating expenses and extend equipment life. These innovations are designed into every Next Generation RM-Series oil-flooded rotary screw air compressor—industry-leading airend enhancements for superior efficiency, world-class delivered capacity and exceptional reliability. All supported by unique advantages, including expert design and engineering, a comprehensive suite of support programs and long-life Ingersoll Rand-branded consumables.

Next Generation RM-Series compressors. The intelligence you need—to win.

Global Presence, Local Service



- Manufacturing Facilities
- Buffalo, NY, US
- Campbellsville, KY, US
- Mocksville, NC, US
- West Chester, PA, US
- Curitiba, Brazil
- Wasquehal, France
- Oberhausen, Germany
- Simmern, Germany

- Fogliano, Italy
- Milan, Italy
- Vignate, Italy
- Ahmedabad, India
- Shanghai, China
- Wujiang, China

- Global Distribution Centers
- Charlotte, NC, US
- Genk, Belgium
- Singapore
- Shanghai, China

Efficient Operation and Powerful Information

We Started At The Core

When we made the Next Generation RM-Series we started with an all-new, state-of-the-art airend, making it your best choice for performance. The new airend improves efficiency as much as 16% through several advancements, including an optimised rotor profile to help minimise operating expenses. The new rotor profile also provides world-class airflow, delivering up to 14% more than previous models. With more airflow for the same power input, your compressor requirements are smaller, reducing both investment costs and energy usage, to lower your total cost of ownership.



Knowledge Is Power


The best compressors deliver air and actionable information. That's why every Next Generation RM-Series compressor includes an intelligent controller that monitors key operations and adjusts system parameters to maximise uptime and minimise energy consumption. It gives you real-time facts to make and execute informed decisions...from virtually anywhere in the world.




For Higher Energy Efficiency

Every RM-Series compressor features an all-new highly efficient airend, in combination with motor meeting IE3 and ECO*-PM IE5 energy-efficiency standards, helping you save up to 12-30% on energy costs.

Every RM-Series compressor features an all-new highly efficient airend, in combination with motor meeting IE3 and ECO*-PM IE5 energy-efficiency standards, helping you save up to 12-30% on energy costs.



Significantly reduce total cost of ownership



Rotary comparison at 79% average volume capacity; 4000 hours per year; 0.05\$/kWh

Luminance Controller

With powerful control and remote management capability, new generation Luminance controller of Ingersoll Rand guarantees steady operation and also greatly improves operating and management efficiency of your unit.



More User-friendly Interface

- High-resolution touch screen:
Le-180, 7.0"; Le-120, 4.3"
- More intuitive key parameter & information display



Easier Upgrade

- Modular design for easier iterative upgrade of software functions and continuous improvement of user experience



More Advanced Algorithm

- Advanced controller algorithm for smaller pressure fluctuation and lower energy consumption
- Sequencer for up to 4 compressors with Luminance and no other system controllers



Steadier Performance

- Fully isolated design with stronger anti-interference capability and better electromagnetic compatibility
- Used in a variety of operating ambient conditions and operating life of at least 40,000 hours for 5 years




More Efficient Management

- Built-in Internet connection for efficient remote management of operating status and maintenance schedule of the unit
- Automatic alarm & fault reminder and performance report sending



Stronger Core

- Multi-core processor for significant improvement of computing speed and communication capability
- Significantly reduce data collection and operation interface delay for more timely communication



Le Controller Features

Service Contract



PackageCARE: when the agreement becomes effective, all operating risks transfer from you to us to free you from any concerns.

You will enjoy 100% of operating risk transfer for any machine model and life.



PlannedCARE: all-round genuine spare parts and maintenance services

You will enjoy preventative diagnosis, current state analysis & trend judgment; 10 years' air end warranty (for new oil-flooded rotary screw air compressor)



PartsCARE: genuine spare parts for daily maintenance

You will enjoy regular shipment of spare parts and daily maintenance reminder, 5 years' air end warranty (for new oil-flooded rotary screw air compressor)

Peace of Mind



Lower TCO

CARE service programs provide the most cost-effective solutions based on your customized maintenance strategy.



Quality Results

Ingersoll Rand factory-trained service technicians are backed by more than 160 years of industry experience.



Increased Uptime

Our CARE programs help decrease unplanned downtime and costly production interruptions.



Efficient Energy Use

Peak system efficiency is achieved through properly performed maintenance and inspection.



Peace of Mind

Our world-class services will help you achieve the results you need, while you focus on what's important to your business,

Maintenance Service Package

| | 2,000 hours Package | 4,000 hours Package | 8,000 hours Package |
|---|---------------------|---------------------------|---------------------------------|
| Replacement/Maintenance Content and Periods | Air filter element | Air filter element | Air filter element |
| | Oil filter element | Oil filter element | Oil filter element |
| | Greasing | Oil-air separator element | Oil-air separator element |
| | | Motor grease | Spare parts package |
| | | | Minimum pressure valve |
| | | | Thermostatic valve care package |
| | | | Inlet air valve care package |
| | | | Water cooler seal care package |
| | | | Motor grease |

Reliability: constant air quality guarantee with genuine spare parts

Scheduling: regular maintenance & care as planned to decrease failure probability and increase operating stability

Efficiency: one chart No. replacing a number of spare parts lists to increase procurement & management efficiency

Comprehensiveness: all parts and components required for maintenance or service at a time are included for shorter lead time than individual parts

Economy: visual service cost budget and superiority in price to purchase of individual parts



One-stop service with OEM quality guarantee

Optimized internal structural design



1 Efficient

All-new, state-of-the-art air ends improve efficiency as much as 16% and airflow by 14%, and are designed for long life and reliable operation.

2 Reliable

Three-stage separation system with conical baffle removes all but 3 ppm of lubricating oil from delivered air—protecting downstream equipment and extending filter life—to maximise productivity and minimise expenses.



3 Robust

V-shield™ technology uses plane-sealed O ring that helps deliver repeatable, leak-free connections.






7 Intelligent

Luminance controller enables real-time system parameter monitoring. Keeps you informed of compressor status and alarms to exempt you from losses due to unexpected sudden shutdown.



6 Reliable / Efficient / Easy to Maintain

Unwelded oil / after-cooler horizontally arranged in parallel on top of the unit decreases distortion & leakage caused by heat stress, increases reliability, extend service life, reduce maintenance work, and reduce customers' use cost during life cycle of the unit and improve their productivity.




5 Motor

Fixed speed drive: premium IEC60034-30 IE3 motor enables IP55 protection grade and Class F insulation with B rise.




Variable speed drive: highly efficient oil-cooled IE5 & IP66 PM motor enables Class H insulation with B rise.



4 Efficient / Superior In Productivity

The air intake system with large-allowance inlet air and low pressure drop air filter effectively reduces inlet air pressure and improve efficiency of the unit, and reduces maintenance work and cost to facilitate the production for customers.



The Airend —the Heart Of Every Compressor




Air compressor use accounts for a significant part of your energy costs. Designed using advanced computer modeling techniques, our team of skilled engineers have optimized the airend to be with 16% higher efficiency, excellent airflow, lower operating noise, longer service life and higher reliability well known in the industry to operate reliably to improve your company's bottom line.

Designed for long life and reliable operation


- 1 Strategically positioned lubrication points efficiently deliver oil exactly where it's needed, improving reliability and lowering power consumption
- 2 Advanced gear transmits drive power more efficiently and reliably

Integral Gearbox

- 3 Integral gearbox reduces windage losses and drivetrain length for more efficient performance and easier serviceability



- 4 Enhanced bearing arrangement reduces resistance and improves power management for maximum reliability and performance
- 5 Maintenance-free, sealed drive system requires no regular service and protects against damaging dirt and moisture



World-class energy efficiency

Advanced Rotor Profile

- 6 Optimised rotor profile helps deliver up to 16% increased efficiency and 14% more airflow, reducing energy cost.

- 7 Lower friction bearing arrangements improve energy efficiency

- 8 Optimised gear lubrication increases reliability and reduces power consumption through strategically injecting oil into gear mesh

- 9 Streamlined inlet and outlet flow passage reduces pressure drops

- 10 Optimised oil-injection process lowers temperature and increases efficiency during compression

Air Treatment


Moisture and contamination in compressed air cause significant problems in equipment operation, such as rust, scale and clogged orifices that result in product damage or costly shutdowns. Making our air treatment equipment an integral component of your compressed air system will improve productivity, system efficiency and product or process quality.

Refrigerated Dryers

Our cost-effective refrigerated dryers provide clean, dry air for most industrial applications. Choose efficient cycling dryers to maximize energy savings or non-cycling dryers for a lower initial cost

Refrigerated Dryer Features

- Dew points as low as 3°C (38°F), meeting ISO Class 4 requirements
- Intuitive microprocessor control for easy operation
- Corrosion-free heat exchanger design for reliable operation
- Compact design for easy serviceability



Desiccant Dryers

Choose desiccant dryers when very low dew points are necessary for high-quality air and to prevent potential freeze-up. Depending on whether you require lower initial capital costs, or lower energy use, choose from heatless, externally heated or heated blower desiccant models.

Desiccant Dryer Features

- Deliver reliable -40°C pressure dew point in most operating conditions
- High-strength desiccant and durable valves
- Low pressure drop design saves energy
- Advanced microprocessor control is easy to use and maximizes uptime

30-75kW Performance

| Model | Max. Pressure | | Nominal Power | | Capacity | | Dimensions(L x W x H) | | Weight(air cooled) | |
|---------------------------|---------------|-----------|---------------|---------|--------------------------|----------|-----------------------|--------------------|--------------------|---------|
| | barg-50Hz | psig-60Hz | kW-50Hz | hp-60Hz | m ³ /min-50Hz | cfm-60Hz | mm-50Hz | in-60Hz | kg-50Hz | lb-60Hz |
| i/ie Standard Performance | | | | | | | | | | |
| RM30ie_A RM30ie_A TAS | 7.5 | 110 | 30 | 40 | 5.6 | 196 | 1544 x 884 x 1376 | 60.8 x 34.8 x 54.2 | 795 | 1753 |
| | 8.5 | 125 | | | 5.3 | 187 | | | | |
| | 10 | 145 | | | 4.6 | 166 | | | | |
| | 14 | 200 | | | 3.6 | 132 | | | | |
| RM37ie_A RM37ie_A TAS | 7.5 | 110 | 37 | 50 | 7.0 | 247 | 1544 x 884 x 1376 | 60.8 x 34.8 x 54.2 | 860 | 1896 |
| | 8.5 | 125 | | | 6.5 | 226 | | | | |
| | 10 | 145 | | | 5.65 | 200 | | | | |
| | 14 | 200 | | | 4.6 | 166 | | | | |
| RM45ie_A RM45ie_A TAS | 7.5 | 110 | 45 | 60 | 8.4 | 293 | 1544 x 884 x 1376 | 60.8 x 34.8 x 54.2 | 930 | 2050 |
| | 8.5 | 125 | | | 7.9 | 275 | | | | |
| | 10 | 145 | | | 7.0 | 247 | | | | |
| | 14 | 200 | | | 5.7 | 201 | | | | |
| RM55i | 7.5 | 110 | 55 | 75 | 10.3 | 342 | 1832 x 1249 x 1512 | 72.1 x 49.2 x 59.5 | 1233 | 2718 |
| | 8.5 | 125 | | | 9.8 | 340 | | | | |
| | 10 | 145 | | | 8.4 | 301 | | | | |
| | 12.5 | 180 | | | 7.5 | 267 | | | | |
| RM75i | 7.5 | | 75 | 100 | 12.8 | | 1832 x 1249 x 1512 | / | 1302 | / |
| | 8.5 | / | | | 12.4 | / | | | | |
| | 10 | / | | | 11.3 | / | | | | |
| | 12.5 | / | | | 10.2 | / | | | | |
| RM75ie | 7.5 | 110 | 75 | 100 | 14.0 | 508 | 1832 x 1249 x 1512 | 72.1 x 49.2 x 59.5 | 1623 | 3578 |
| | 8.5 | 125 | | | 13.5 | 490 | | | | |
| | 10 | 145 | | | 12.5 | 455 | | | | |
| | 12.5 | 180 | | | 10.5 | 381 | | | | |
| n/ne Standard Performance | | | | | | | | | | |
| RM30n_A | 10 | * | 30 | 40 | 1.2-5.6 | * | 1544 x 884 x 1376 | * | 602 | * |
| RM37n_A | 10 | * | 37 | 50 | 2.1-7.0 | * | 1544 x 884 x 1376 | * | 692 | * |
| RM45n_A | 10 | * | 45 | 60 | 2.1-8.5 | * | 1544 x 884 x 1376 | * | 692 | * |
| RM55n_A | 10 | * | 55 | 75 | 2.9-10.2 | * | 1832 x 1249 x 1512 | * | 978 | * |
| RM75ne_A | 10 | * | 75 | 100 | 4.1-15.4 | * | 1832 x 1249 x 1512 | * | 1291 | * |
| RM30n_A TAS | 10 | * | 30 | 40 | 1.2-5.6 | * | 2200 x 884 x 1376 | * | 804 | * |
| RM37n_A TAS | 10 | * | 37 | 50 | 2.1-7.0 | * | 2200 x 884 x 1424 | * | 894 | * |
| RM45n_A TAS | 10 | * | 45 | 60 | 2.1-8.5 | * | 2558 x 884 x 1424 | * | 905 | * |

1. Displacement (FAD*)(volume flow) is the operating parameter of the complete, measured according to the test standard of ISO1217:2009 Appendix C;
2. * means to be published, / means not applicable

30-75kW Configuration

| Standard Configuration Category | Description | Fixed Speed | Variable Speed |
|--------------------------------------|---|-------------|----------------|
| | | i/ie | n/ne |
| Airend | Airend of excellent performance | ● | ● |
| Controller | Energy-saving controller, available in two languages | ● | ● |
| | Programmable start-stop operation and remote connection | ● | ● |
| | Built-in sequence control program to jointly control up to 4 compressors ⁽¹⁾ | ● | ● |
| | Standard Modbus RTU protocol, RS485 interface | ● | ● |
| Active adaptive protection (PAC™) | Power off and restart (PORO) ⁽²⁾ | ● | ● |
| | Monitor maintenance for filter element and other wearing parts and correspondingly adjust system operating parameters | ● | ● |
| Cooling system | Real-time electronic maintenance indicator and stoppage protection | ● | ● |
| | Highly efficient, energy saving and low noise fan | ● | ● |
| V-Shield™ technology | Shock-absorbing pads and high-class flexible metal hose | ● | ● |
| | Recyclable fluorinated material for non-leakage seal | ● | ● |
| Auxiliary system | Noise-reducing housing of the unit | ● | ● |
| | Anti-drip stand | ○ | ● |
| | Long-lasting filter element and separator element | ● | ● |
| | Full-load/no-load flow regulation system control | ● | \ |
| | Variable-frequency PID adjustment control | \ | ● |
| Master motor & electrical system | Star triangle buck starter | ● | \ |
| | Variable-frequency step-down start | \ | ● |
| | High efficiency enclosed TEFC, IP55 electric motor – Grade B temperature rise, Class F insulation | ● | \ |
| General configuration | Variable-frequency PM TEFC, IP66 electric motor – Grade B temperature rise, Class H insulation | \ | ● |
| | Simple single air inlet-outlet pipeline (single air inlet and single air outlet) | ● | ● |
| 12-month warranty program | | ● | ● |
| Options | | | |
| Protection against harsh environment | High temperature protection (up to 55 C) ⁽³⁾ | ○ | \ |
| | Dusty intake air filter | ○ | ○ |
| | Electric control box heater (55-75kW) | \ | ○ |
| Environment-friendly option | Food-grade coolant Ultra FG | ○ | ○ |
| Water-cooled unit | Water-cooled unit (55-75kW) | ○ | ○ |

● Standard ○ Optional \ Not applicable

- (1) To be realized after software update
- (2) With standard software and non-standard buzzer
- (3) 55kW unit can reach the temperature



Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our portfolio of products consists of air compressors, pumps, blowers, and systems for fluid management, loading and material handling as well as power tools. With over 16,000 employees globally, our team develops customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRco.com.



Contact Ingersoll Rand

Add.: F11, L'Avenue, 99 Xianxia Road, Shanghai

Tel.:021-2221 6000

Website: www.ingersollrand.com

24小时全国免费服务热线:

800 820 2128

400 820 2128