



2235 SERIES

1/2" Impact Wrench

THE BAR DOESN'T RAISE ITSELF.

The 2235 Series 1/2" Impact Wrench

A powerful, durable and reliable workhorse whose reputation is built on helping you build yours. It's been rigorously tested, beaten up, dropped and pushed to the limits to make sure it will always work when you need it most. The 2235 Series is incredibly powerful, durable and reliable so that it delivers every time you need REAL WORK done right.



General Automotive



General Industrial



Heavy Equipment Repair



Facility Maintenance

TOOL FEATURES

DURABILITY

Born from the legendary durability of the Ingersoll Rand 2135 Series, the 2235 pushes toughness to the next level. It's built with a titanium hammercase, steel-wear plate and composite housing that protect the tool from the harshest environments

POWER

Punish the toughest bolts with 1,350 ft.-lbs. of nut-busting torque and 930 ft.-lbs. of max reverse torque powered by Ingersoll Rand's finely tuned twin-hammer impact mechanism. From the garage to the most demanding industrial sites, there is no job that will stand in its way



RELIABILITY

Every component, every mechanism and every function of the 2235 Series has been pushed to the limits to ensure it always performs in the face of the toughest jobs. Backed by a two-year warranty, the 2235 Series is a finely tuned workhorse, from its components to its technology, to be the impact wrench you can always count on to get REAL WORK done

WEIGHT

At only 4.6 pounds, no other impact wrench on the market can match the combined power and weight of the 2235 Series. With less weighing you down, you can work harder and faster for longer stretches of time

SPECS

2235 SERIES 1/2" IMPACT WRENCH

Model	Drive Size, Type	Max Torque ft.-lb. (Nm)	Nut-Busting Torque ft.-lb. (Nm)	BPM	Free Speed (rpm)	Weight lb (kg)	Length in. (mm)	Sound Level dB(A)
223QTIMAX-2	1/2"	930 (1260)	1350 (1830)	1220	8500	4.6 (2.1)	7.6 (193)	98
2235TiMAX-2	1/2", 2" Ext.	930 (1260)	1350 (1830)	1220	8500	4.9 (2.2)	9.6 (244)	98
2235QTIMAX	1/2"	900 (1220)	1300 (1760)	1220	8500	4.7 (2.1)	7.6 (193)	88.7
223QTIMAX-2	1/2", 2" Ext.	900 (1220)	1300 (1760)	1220	8500	5.0 (2.3)	9.6 (244)	88.7

Performance at 90 PSI. Air inlet NPTF 1/4" (6mm). Min hose size 3/8" (10mm). Average air consumption 6 cfm (170l/min)



Learn more at www.ingersollrand.com

Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency.

©2022 Ingersoll Rand PTL_001_03_2021_2235TiMAX